

Panel PC PJLOR

- Equipped with 4-core ARM architecture A55 processor and Android 12 operating system
- Full 10.1-inch HD display, the IP65-rated front panel protects against water and dust ingress
- Fanless design, excellent in heat dissipation and strong stability performance
- Wide voltage and temperature working performance, perfect for 24/7 use in all weather conditions
- Rich interfaces, including multiple USB/RS232/LAN/HDMI and other I/O ports, easily meet various scenario requirements
- MiniPCIE slot, can be expanded with communication modules, solid-state drives and other peripherals
- Support 802.11b/g/n/ac protocol, dual Wi-Fi antennas and Bluetooth 5.0
- Standard PPC mounting hook component, easy to install and supports various installation methods such as embedded and wall-mounted





RK3568 Quad core




Android 12 Operating System



10.1 inch screen



700cd/m² Brightness




800*1280 Screen resolution



WiFi



Running 24/7 without affecting reliability



Rich interface extensions



storage expansion



IP65

Panel PC P10R

INERUgged

Specifications







Memory

RAM: 4GB onboard ROM: 64GB



Display

Type: LCD Size: 10.1 inch 16:10 Resolution: 800×1280 Brightness:700 cd/m²



Touch Pannel



Dimension/Weight

257.2*170*45.95mm 1.2kg



Internet

Dual-band WiFi/BT5.0



Standard USB-A USB3.0*1 + USB3.0*1 OTG + USB2.0*2 Power interface DC IN 12V-24V Power connector *1 Standard Earphone Jack *1

RJ45 *1 DB9 PORT RS232 *2 HDMI *1



Front panel IP65

Rugged Features

Working temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Humidity: 95% Non-Condensing




AC100V ~ 240V、50Hz/60Hz output DC 12V/4A











* The technical specifications of this product are subject to change without prior notice



© Tel: 400-830-4882

www.onerugged.com

□ inquiry@onerugged.com

Room 401, Building C, Chaojie Industrial Park, No. 1 Guanghui Road, Jinsha Community, Kengzi Street, Pingshan District, Shenzhen, China