



N14M

Enterprise-Grade Rugged Notebook

- The Intel® Core™ Ultra processor, with a dedicated AI engine (NPU)
- 14-inch fully laminated display, supports optional 10-point touch and glove touch
- High-speed Thunderbolt 4 interface, HDMI 2.0, USB, RJ45, RS232, etc.
- Intel® Arc™ integrated graphics with Xe LPG architecture
- Windows 11 OS, dual memory/dual storage slots
- 53Wh + 14.4Wh dual batteries, large battery is removable



Durability	- MIL-STD-810H certified 4ft, 26 drops (each side, edge, and corner) - IP65 compliant ±4kV contact discharge, ±8kV air discharge
Operating System	- Windows 11 Pro - Optional Windows 11 Home/IOT
Processor	- Intel Ultra 7 155H (24MB cache, up to 4.8 GHz,16 cores, 22 threads, TDP 28W) - Optional Intel Ultra 5 125H (18MB cache, up to 4.5 GHz, 14 cores, 18 threads, TDP 28W)
Graphics	Intel Xe LPG Graphics
Memory	16GB DDR5 SO-DIMM - Optional 32GB DDR5
Storage	256GB PCIe SSD - Optional 512GB/1TB SSD
Display	14.0" FHD (1920x1080), 1000 nits sunlight readable display - Optional 10-point capacitive touch screen, supports glove touch mode
Audio	- Integrated microphone - Integrated 3W speaker - Class K
Camera	MF 5.0 MP front camera
Keyboard & Input	- Touchpad x1 - KB (US) x1 - Optional KB (DE)/KB (FR)/KB (EU) 4 buttons
Network & Connectivity	- Intel® Wi-Fi 6E (802.11 ax) - Bluetooth® 5.3 - Optional 4G LTE - LTE-FDD: B1/3/5/7/8/20/28 - LTE-TDD: B38/40/41 - WCDMA: B1/5/8 - GSM: / - Optional 5G - GPS module

Security	- Integrated TPM2.0 - Optional HF-RFID (NFC) reader - Fingerprint scanner - Kensington lock
I/O Interface	- Micro SD card x1 - SIM card x1 - USB 3.2 Gen 2 (Type-A) x1 - Thunderbolt 4 (Type-C) x1 3.5mm audio jack x1 - HDMI 2.0a mini x1 10/100/1000 Ethernet (RJ45) x2 - Optional 12-pin Pogo pin x1 (charge & USB) - USB 3.2 Gen 1 (Type-A) x1 - USB 2.0 (Type-A) x1 - Serial port (RS232: D-sub, 9-pin) x1 5.5mm DC in jack x1
Expansion Module	- Optional 2nd NVME PCIe SSD - Optional user-definable PCIe module
Battery & Charging	- AC adapter: 100-240V, 50Hz-60Hz, 71.82W (19V/3.78A) - Li-ion battery, 11.4V, 4700mAh, 7h10min - Li-ion battery, 11.1V, 1300mAh - Separate RTC 3V/210mAh
Environment	- Operating temperature: -20°C to 60°C (-4°F to 140°F) - Storage temperature: -30°C to 70°C (-22°F to 158°F) - Humidity: 95% (non-condensing)
Dimension	363.2 mm(L) × 287.4 mm(W) × 42.1 mm(H)
Weight	2.97kg
Accessories	- Standard: Adapter, Removable battery - Optional: Quad charging dock
Warranty	One-year limited warranty standard

1. Please contact your sales representative for feature availability.
2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Standard



Adapter



Removable Battery

Optional



Quad Charging Dock

CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314)
Tel: +86-(0)755-2372 2880 Email: marketing.info@emdoor.com
Web: www.emdoorugged.com Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen

